

TATA PRIMA 6038

SPECIFICATIONS

Model	Cummins ISLe	Parking brake	Hand Operated air assisted Spring actuated parking brake acting on rear wheels
Capacity (cc)	8898 cc	Anti-lock braking system (ABS)	Yes
Туре	4-stroke diesel engine	MAJOR DIMENSIONS	
Power	370 BHP @ 2100 r/min (+/-50 r/min)	Wheelbase (mm)	4275 mm
		MASS	
Torque Nm @ r/min	1550 Nm @ 1200-1400 r/min	GVM (kg)	49500 (GCW)
TRANSMISSION		GCM (kg)	60 Ton
Model	EATON FS010309-0D	Manufactures Rear axle weight (kg)	18 T
No. of gears forward & reverse	9 F+ 1 R Manual	Manufactures Front axle	757
STEERING		weight (kg)	7.5 T
Туре	Power steering	FUELTANK	
Turning radius	7.75 m	Fuel Tank Capacity (Ltrs)	365 L
DRIVE AXLE		TYRES	
Reduction type	Planetary Hub reduction	Size & Ply rating	315/80R22.5
Rear Axle	TATA RA-210HR-T	No. of tyres	10 + 1 spare
CLUTCH		ELECTRICALS	
Type		Working Voltage	24 V
	Single plate, dry friction type	Batteries	2x12V, 150 Ah
Diameter (mm)	430 mm	Air conditioner	HVAC
BRAKES			
Туре	All Air Dual Circuit - S Cam with ABS		

Corporate Office: Tata Motors Limited, 4th Floor, Ahura Centre, 82, Mahakali Caves Road, MIDC Andheri (East), Mumbai 400093 Website: www.tatamotors.com | Customer Helpline: cac@tatamotors.com Tel.: 022 62407101/ 022 62407109 | Toll-free: 1800-209-7979 | Fax: 022 6240 7100